

Poster presentation

Decoding the population dynamics underlying ocular following response using a probabilistic framework

Laurent U Perrinet* and Guillaume S Masson

Address: UMR6193 CNRS – Univ. Aix-Marseille, France

Email: Laurent U Perrinet* - Laurent.Perrinet@incm.cnrs-mrs.fr

* Corresponding author

from Eighteenth Annual Computational Neuroscience Meeting: CNS*2009
Berlin, Germany. 18–23 July 2009

Published: 13 July 2009

BMC Neuroscience 2009, **10**(Suppl 1):P359 doi:10.1186/1471-2202-10-S1-P359This abstract is available from: <http://www.biomedcentral.com/1471-2202/10/S1/P359>

© 2009 Perrinet and Masson; licensee BioMed Central Ltd.

Introduction

The machinery behind the visual perception of motion and the subsequent sensorimotor transformation, such as in Ocular Following Response (OFR), is confronted with uncertainties, which the primate's visual system efficiently resolves. We may understand this response as an ideal observer in a probabilistic framework by using Bayesian theory [1] that we previously proved to be successfully adapted to model the OFR for different levels of noise with full field gratings or with disk of various sizes and the effect of a flickering surround [2]. More recent experiments of OFR have used disk gratings and bipartite stimuli that are optimized to study the dynamics of center-surround integration. We quantified two main characteristics of the global spatial integration of motion from an intermediate map of possible local translation velocities: (i) a finite optimal stimulus size for driving OFR, surrounded by an antagonistic modulation and (ii) a direction selective suppressive effect of the surround on the contrast gain control of the central stimuli [3]. Herein, we extended in the dynamical domain the ideal observer model to simulate the spatial integration of the different local motion cues within a probabilistic representation. We present analytical results showing that the hypothesis of independence of local measures can describe the initial segment of spatial integration of motion signal. Within this framework, we successfully accounted for the dynamic contrast gain control mechanisms observed in the behavioral data for center-surround stimuli. However,

another inhibitory mechanism had to be added to account for suppressive effects of the surround.

We explore here a hypothesis where this could be understood as the effect of a recurrent prediction of information in the velocity map. In fact, in previous models, the integration step assumes independence of the local information while natural scenes are very predictable: due to the rigidity and inertia of physical objects in visual space, neighboring local spatiotemporal information is redundant and one may introduce this *a priori* knowledge of the statistics of the input in the ideal observer model. We implement this in a realistic model of a layer representing velocities in a map of cortical columns, where predictions are implemented by lateral interactions within the cortical area. First, raw velocities are estimated locally from images and are propagated to this area in a feed-forward manner. Using this velocity map, we progressively learn the dependence of local velocities in a second layer of the model. Results show that this simple model is sufficient to disambiguate characteristic patterns such as the Barber-Pole illusion. Due to the recursive network that modulates the velocity map, it also explains that the representation may exhibit some "memory," such as when an object suddenly disappears or when presenting a dot followed by a line (line-motion illusion). We will relate this emergent property of the motion perception system to the concept of second-order motion.

Acknowledgements

This work was supported by EC IP project FP6-015879, FACETS.

References

1. Weiss Y, Simoncelli EP, Adelson EH: **Motion illusions as optimal percepts.** *Nature Neuroscience* 2002, **5**:598-604. doi:10.1038/nn858.
2. Perrinet L, Masson GS: **Modeling spatial integration in the ocular following response using a probabilistic framework.** *J Physiology (Paris)* 2007.
3. Barthelemy F, Perrinet LU, Castet E, Masson GS: **Dynamics of distributed 1D and 2D motion representations for short-latency ocular following.** *Vision Research* 2007, **48**:501-22. doi:10.1016/j.visres.2007.10.020.

Publish with **BioMed Central** and every scientist can read your work free of charge

"BioMed Central will be the most significant development for disseminating the results of biomedical research in our lifetime."

Sir Paul Nurse, Cancer Research UK

Your research papers will be:

- available free of charge to the entire biomedical community
- peer reviewed and published immediately upon acceptance
- cited in PubMed and archived on PubMed Central
- yours — you keep the copyright

Submit your manuscript here:
http://www.biomedcentral.com/info/publishing_adv.asp

